

NEC Analogue Phones have been designed to simplify the way you communicate.



AT21 Analogue Phone

Expand the reach of your NEC Xen and NEAX system with an affordable and reliable AT 21 analogue phone solution. Perfect for areas of your business that don't require the power and features of a digital multiline phone, the AT21 analogue phone provides a simple, high quality solution for areas such as corridors, lobbies and warehouses. And with a dedicated data jack for connecting a computer with a modem, it's an ideal choice for hotel guest rooms.

Affordable, Reliable, Quality

With a host of basic system features including voicemail, paging and transfer to name a few, the AT21 provides your business with an ideal solution to keep low traffic areas connected with affordable, reliable, quality.

The AT21 analogue phone is built for plug-and-play integration with any member of the Xen or NEAX families of communication systems - the NEAX 2400 IPX, the NEAX 2000 IPS, and Xen system series.

AT21 features include:

- Hearing Aid Compatibility
- Receive Call Volume Control
- Ring Volume Control
- Large Message Waiting Indicator Lamp
- Last Number Redial

AT21 Specifications

- **Colour** Black with silver overlay
- **Power Source** Line Powered
- **Dial Mode** Selectable DP (Pulse) or DTMF (Tone)
- **Redial One Touch** Up to 31 Digits
- **Dimensions** 224mm x 165mm +/- 5mm (Length x Width)
- **Function Buttons** Hookflash, Program and Redial Keys
- **Message Waiting Lamp** Neon Lamp, Glow Through Filter Raised from Surface, Incoming Ring Indication
- **Ringer Tone** Slow, Medium, Fast, Off
- **Ring Volume Control** 3 Levels (Soft, Medium, Loud)
- **Handset Receiver Volume** 6 Levels (Volume Key)
- **Handset Curly Cord** 3m
- **Telephone Line Cord** 3 Metres
- **Dedicated Data Jack**
- **Wall-Mount Unit** Built-in
- **Approvals:**
 - EN55022:1998 + A1:2000
 - AS/NZS3548: 1995 A2: 1997 (CISPR 22:1993)
 - ACA TS001: 1997
 - AS/NZS 3260:1993 + A1/1995, A2/1995, A3/1996, A4/1997
 - AS/ACIF S003:2001
 - AS/ACIF S004:2001
 - AS/ACIF S006:2001

Empowered by Innovation

NEC

NEC Analogue Phones have been designed to simplify the way you communicate.



AT30 Analogue Phone

A hard working, versatile solution, the AT30 provides simple feature access in a cost effective, streamlined package. An ideal alternative to a multiline digital phone when feature access is required at a lower cost – the AT30 speakerphone delivers access to a host of time saving features in a streamlined economical package.

One Touch Simplicity

Access to frequently dialled numbers and features is made simple through 15 one touch memory keys, while a two way speakerphone ensures a perfect solution for those areas of the business that require a hands on approach.

With a built in message waiting indicator and parallel connection for modem and fax, the AT30 provides a perfect solution for hotel guest rooms and conference centres.

AT30 Features Include:

- 15 One touch MEMORY keys for frequently dialled numbers
- Make and receive calls HANDS-FREE
- LCD display for dialled number, call timer and clock
- FLASH key to access
- PBX features such as hold & transfer, call back, conference, call pick up, call waiting, etc.
- Message waiting / ring indicator LAMP
- Last number REDIAL key
- MUTE key to temporarily switch off handset and speakerphone microphones

- Handset, speaker, ringer VOLUME controls plus tone selector
- A parallel connection for modem, fax, etc
- Wall mountable

AT30 Specifications

- **Colour** Light grey
- **Power Source** Line powered (there is the option to install 2 AA size batteries to back-up the clock and one touch memories)
- **LCD Display** 16 Character
- **Dial Mode** Selectable DP (Pulse) or DTMF (Tone)
- **Redial One Touch** Up to 32 digits
- **Ringer Tone** Low/mid/high
- **Call /Message Lamp** Neon Lamp, Glow Through Filter Raised from Surface, Incoming Ring Indication
- **Telephone Line Cord** 2 Metres
- **Telephone Handset** Hearing aid compatible
- **Two-way Handsfree** Loudspeaker and microphone
- **Function Buttons** Program, Flash, Redial/Pause, Mute, Speaker Keys
- **Operating Temp.** 0° to 40°C
- **Environment Humidity** 20% to 90% RH
- **Dimensions** 225L x 160W x 80H (mm)
- **Weight** 650gm
- **Wall Mounting** Two wall mounting screws included
- **Approvals:**
 - EN55022:1998 + A1:2000
 - AS/NZS3548: 1995 A2: 1997 (CISPR 22:1993)
 - ACA TS001: 1997
 - AS/NZS 3260:1993 + A1/1995, A2/1995, A3/1996, A4/1997
 - AS/ACIF S003:2001
 - AS/ACIF S004:2001
 - AS/ACIF S006:2001

Empowered by Innovation

NEC